










ADD: QiHang Building, No.5059 SongBai Road, GuangMing District, Shenzhen, China
 Tel: +86 135 1091 4995 E-mail: Peter@onature.cc Website: www.onature.cc

Photo	Name	Main specs	Notice	Price USD/PCS
	6 Mosfet KT Controller	1.Voltage :36V / 48V 2.Max Current: 17A 3.Rated Current: 8A 4.Power: 250W / 350W 5.Product Size: 94mm*61mm*38mm 6.With 5 kinds connectors: -Battery connector Bullet -1T4 cable 8pin -PAS sensor -Ebike motor 9 pin	Only compatible with KT Display LCD3 LCD4 LCD5 or LCD8	23
	9 Mosfet KT Controller Battery Bullet or XT60 Connector	1.Voltage :36V / 48V 2.Max Current: 22A 3.Rated Current: 11A 4.Power: 350W / 500W 5.Product Size: 130mm*65mm*38mm 6.With 5 kinds connectors: -Battery connector Bullet or XT60 -1T4 cable 8pin -PAS sensor -Ebike motor 9 pin	Only compatible with KT Display LCD3 LCD4 LCD5 or LCD8	29
	KT Display LCD5 with Junlet Waterproof end	1.Voltage : 24V / 36V / 48V 2.Cable Length: 40cm 3.Show Data: TM, TTM, Km/H, MPH, MXS, AVS, Km, Mil, DST, ODO, VOL 4.With Cruise and Reverse function	It only fits KT series controllers	23
	KT Display LCD4 with Junlet Waterproof end	1.Voltage : 24V / 36V / 48V 2.Cable Length: 40cm 3.Show Data: TM, TTM, Km/H, MPH, MXS, AVS, Km, Mil, DST, ODO, VOL 4.With Cruise and Reverse function	It only fits KT series controllers	17

	KT 12 Magnets PAS Sensor with Junlet Waterproof end	1.Magnet : 12 Magnets 2.Installation : Left 3.Voltage : Use with 36V 48V controller 4.Cable Length : 90cm 5.Connector : 3Pin Junlet Male	1.Please set the parameter C1=07 2.Must install on left side	6.3
	Hydraulic Brake Sensor for KT Controller	1.Cable Length: 40cm 2.Connector : 3Pin Junlet Female 3.Including: 2pcs sensors,2pcs magnets	Package include 1pair (2pcs)	9
	Wuxing Thumb Throttle with Junlet Waterproof end	1.Cable Length: 30cm 2.Connector : 3Pin Junlet Male 3.Thumb Throttle: Wuxing 130X	It only fits KT series controllers	5.3
	Wuxing Brake Lever with Junlet Waterproof end	1.Cable Length: 40cm 2.Connector : 3Pin Junlet Female 3.Brake Lever: Wuxing 115PDD 4.Including: 2pcs brake levers	Package include 1pair (2pcs)	7.7
	Junlet 1T4 Cable for KT Controller	1.Main Connector: 8 pin,Junlet made 2.Cable Length: 120cm 3.Four Connectors: -Two male connectors for brake sensor or brake lever -One 3pin female connector for thumb throttle -One 5pin female connector forKT displya LCD4 or LCD5	Only compatible with parts with Junlet connector	5.9
Remark: 1.Above quotation are EXW price,not include shipping cost. 2.The quotation based on quantity 10pcs-50pcs.if order more.can get more discount.				

ADD: QiHang Building, No.5059 SongBai Road, GuangMing District, Shenzhen, China
 Tel: +86 135 1091 4995 E-mail: info@onature.cc Website: www.onature.cc











Photo	Name	Main specs	Notice	Price USD/PCS
	ON-EB200, Ebike light for Bafang middle Motor	<ol style="list-style-type: none"> 1. Power:2.4W 2. Brightness:200 lumens 3. Input voltage: DC6V, 12V (Bafang BBS02 BBSHD Mid motor output 6V 2.4W for headlight) 4. Material:CNC Aluminum 5. Product size:38*38*42mm 6 Wire:Length 100cm 7. IPX5 waterproof, heavy rain waterproof 	Fits for all ebikes motor provide output 6V / 12V 2.4W /3W for headlight.	13.2
	ON-EB100, Ebike headlight powerful	<ol style="list-style-type: none"> 1. Power:5W 2. Input:DC12V to 62V 3. Brightness:300 lumen 4. Material:Aluminum, high quality ebike light. 5. Product size:50*50*60mm 6. Wire: Length 1 meter 7. With horn or button on back 	Power is 5W, not fits for some kinds middle drive motor which only provide 3W for headlight.	7.9
	ON-EB300, Ebike front light can install on handlebar and fork	<ol style="list-style-type: none"> 1. Power: 4W 2. Input: DC12V - 62V 3. Brightness:250 lumen 4. Material:Plastic, light weight. 5. Wire:Length 1 meter 6. IPX4 waterproof, rain waterproof 7. With horn 	Power is 4W, not fits for some kinds middle drive motor which only provide 3W for headlight.	6.9
	ON-EB60, Ebike headlight with 3pcs LED	<ol style="list-style-type: none"> 1. Use 4pcs LED, provide 250 lumen 2. Power : 4W 3. Work voltage:18V 24V 36V 48V 4. Cable length:1.5m 5. Size:60*60*50mm 6. With horn 	Power is 4W, not fits for some kinds middle drive motor which only provide 3W for headlight.	3.9

Photo	Name	Main specs	Notice	Price USD/PCS
	Ebike rear light with 320 degree beam angle	1. Power:0.6W or 3W , powerful taillight 2. Input:DC6V-62V 3. Cable length:95 cm 4. Two installation screw distance:50mm 5. Material:Plastic,light weight. 6. IPX5 waterproof,heavy rain waterproof	Fit for mounts holes 50mm	6.5
	Ebike rear light	1. Ebike tail light Power:0.6W or 3W 2. Input:DC6V-62V 3. Cable length:100 cm 4. Two installation screw distance:50mm 5. Material:Plastic,light weight.	Fit for mounts holes 50mm	5.5
	Ebike rear light	1. Ebike tail light Power: 3W 2. Work voltage:12V 24V 36V 48V 3. Cable length:1.2m 4. Two installation screw distance: 50mm or only one screw to fix,the screws are adjustable 6. Material:Plastic,light weight.	Fit for mounts holes 50mm or 1 hole mount	4.5
	AAA Battery Bike Rear Rack Light	1. Use 4pcs high quality LED 2. With 2 modes, steady and flashing 3. Use 2pcs AAA batteries,easy replace (Battery not included) 4. Up to 60-80 hours 5. Distance between 2 screws: Adjustable,from 50mm to 70mm is ok.	Fits for many kinds bike rack / Cairrier	2.7
	Ebike headlight + horn switch	1.For handlebar size:22.5mm 2.Product size:L50*W22*H42MM 3.Waterproof:IP65 4.Function:Control headlight horn and ebike light ON/OFF. 5.Cable length:1.5 m	Hot seller	2.9
	Ebike headlight + horn + turning signal switch	1.For handlebar size:22.5mm 2.Product size:L27*W54*H54MM 3.Waterproof:IP65 4.Function:Control headlight horn and turn signal light 5.Cable length:1.5 m	Hot seller	4.5
Remark: 1.Above quotation are EXW price,not include shipping cost. 2.The quotation based on quantity MOQ 100pcs,if order more,can get more discount.				

ADD: QiHang Building, No.5059 SongBai Road, GuangMing District, Shenzhen, China
 Tel: +86 135 1091 4995 E-mail: Peter@onature.cc Website: www.onature.cc









Photo	Name	Main spcs	Connectors	Price USD/PCS
	6 Mosfet KT Controller	1.Voltage: 24V / 36V 2.Max Current: 17A 3.Rated Current: 8A 4. Power: 250W / 350W 5.Product Size: 94mm*61mm*36mm 6. Motor Connector: Bullet Cables 7.Notice: Only compatible with KT Display LCD3 LCD4 LCD5 or LCD8	-Hall sensor wire -Battery cable(XT60) -Throttle -PAS Sensor -Speed sensor -Brake connector (2pcs) -Light connectr 1	20
	9 Mosfet KT Controller	1.Voltage :36V / 48V 2.Max Current: 25A 3.Rated Current: 12A 4. Power: 350W / 500W 5.Product Size: 127mm*67mm*40mm 6. Motor Connector: 3phase cables 7.Notice: Only compatible with KT Display LCD3 LCD4 LCD5 or LCD8	(Output power only 3W) -Light connector 2 (Output big,connect battery directly) -Electric lock -Display -Reverse -Cruise	23
	12 Mosfet KT Controller	1.Voltage :36V / 48V 2.Max Current: 30A 3.Rated Current: 15A 4. Power: 750W / 1000W 5.Product Size: 170mm*83mm*42mm 6. Motor Connector: 3phase cables 7.Notice: Only compatible with KT Display LCD3 LCD4 LCD5 or LCD8	-Hall sensor wire -Battery cable(XT60) -Throttle -PAS Sensor -Speed sensor -Brake connector (2pcs) -Light connectr 1	36
	18 Mosfet KT Controller	1.Voltage :36V / 48V 2.Max Current: 45A 3.Rated Current: 22A 4. Power: 1000W / 1500W 5.Product Size: 235mm*80mm*40mm 6. Motor Connector: 3phase cables 7.Notice: Only compatible with KT Display LCD3 LCD4 LCD5 or LCD8	(Output power only 3W) -Light connector 2 (Output big,connect battery directly) -Electric lock -Display -Reverse -Cruise	39

Photo	Name	Main spcs	Connectors	Price USD/PCS
	KT Display LCD3 with SM Connector 5pin	1.Voltage : 24V / 36V / 48V 2.Cable Length: 160cm 3.Show Data: TM,TTM,Km/H,MPH,MXS,AVS,DST, ODO,VOL 4.With Cruise and Reverse function 5.Show motor temperature.	It only fits KT series controllers	25
	KT Display LCD5 with SM Connector 5pin	1.Voltage : 24V / 36V / 48V 2.Cable Length: 160cm 3.Show Data: TM,TTM,Km/H,MPH,MXS,AVS,DST, ODO,VOL 4.With Cruise and Reverse function		19
	KT Display LCD4 with SM Connector 5pin	1.Voltage : 24V / 36V / 48V 2.Cable Length: 160cm 3.Show Data: TM,TTM,Km/H,MPH,MXS,AVS,DST, ODO,VOL 4.With Cruise and Reverse function		15
	KT 12 Magnets PAS Sensor	1.Magnet : 12 Magnets 2. Installation : Left 3.Voltage : Use with 36V 48V controller 4.Cable Length : 90cm 5.Connector : 3Pin SM Female Connector	1.Please set the parameter C1=07 2.Must install on left side	4.9
	Hydraulic Brake Sensor for KT Controller	1.Cable Length: 165cm 2.Connector : Male SM 2 Pin 3.Including: 2pcs sensors,2pcs magnets 4.Application type: Hydraulic or Mechanical Brake	Package include 1pair (2pcs)	6.9

Photo	Name	Main spcs	Connectors	Price USD/PCS
	Wuxing Thumb Throttle	1.Cable Length: 160cm 2.Connector : 3Pin Male SM Connector 3.Thumb Throttle: Wuxing 130X	Green cable is for signal	4.5
	Wuxing Twist Throttle	1.Cable Length: 160cm 2.Connector : 3Pin Male SM Connector 3.Half Twist Throttle: Wuxing 192X	Package include the grip ,can be full twist too	4.8
	Juniet waterproof motor extension cable	1.Cable Length: 60cm 2.Connector : 9pin Male-Female 3.For 500W 350W Motor	Only compatible with Juniet cable from motor	4.2
	Juniet motor extension cable normal	1.Cable Length: 60cm 2.Connector : 9pin Female waterproof 3.For 500W 350W Motor	Only compatible with Juniet cable from motor	3.9
Remark: 1.Above quotation are EXW price,not include shipping cost. 2.The quotation based on quantity 10pcs-50pcs.if order more,can get more discount.				

ADD: QiHang Building, No.5059 SongBai Road, GuangMing District, Shenzhen, China
Tel: +86 135 1091 4995 E-mail: Peter@onature.cc Website: www.onature.cc





Photo	Name	Main specs	Notice	Price USD/PCS
	Bafang Gear Shift Sensor	1. Operating voltage: 4-5.5 VDC 2. Current consumption: 15mA 3. Signal Output: Pulse duration 0.5s 4. Protection circuit: Short Circuit & Polarity Reversed Protection 5. Housing material: Intensive ABS 6. Waterproof: IP67 7. Connector: 3 pin yellow color 8. Cable: 42cm	Only compatible with Bafang BBS01 BBS02 BBS03B BBSHD middle motor	11
	Bafang Hydraulic Brake Sensor	1. Compatible with all Hydraulic or Mechanical operated brakes. 2. Waterproof connectors with 3 Pin 3. Front & Back Brake sensor. 4. Compatible with all Bafang Mid Drives motor BBS01, BBS02, BBSHD 5. Cable length: 70.4 cm (except sensor and connector)	1. Only compatible with Bafang BBS01 BBS02 BBS03B BBSHD middle motor 2. Package include two pieces (1 pair)	7.7
	USB Programming Cable for Bafang	1. Make the throttle act as a throttle should instead of like an on/off switch. 2. Reduce current draw from 25 amps to 18 amps without impacting performance to increase battery and motor life. 3. Enable full throttle in PAS levels 1-9, throttle over ride of max set speed limit (max speed only applies to PAS).	Only compatible with Bafang BBS01 BBS02 BBS03B BBSHD middle motor	5.9
	Ebike Display Extension Cable for Bafang	1. Cable Length: 57cm 2. Can choose: Male-Male, Female-Female, Male-Female	Only compatible with Bafang BBS01 BBS02 BBS03B BBSHD middle motor display	2






Photo	Name	Main spcs	Notice	Price USD/PCS
	Ebike 1T4 Cable for Bafang	1.Including connectors: Display (Male Connector), Brake Levers (Female Connectors), Thumb Throttle (Male Connector). 2.Cable Length: 77cm or 137cm 3.Main connector is 8pin for Bafang motor	Only compatible with Bafang BBS01 BBS02 BBS03B BBSHD middle motor	5
	3Pin Y-Splitter 1T2 Cable for Bafang	1.Cable Length: 20cm or 50cm 2.Connector : one side is 3pin Male,the other two connectors are Female.	Higo cable,only compatible with Higo cable	3
	Wuxing Twist Throttle for Bafang	1.Cable Length: 50cm 2.Connector : 3Pin Female Higo Cable 3.Choice: Half twist right / left, Full twist right / left	Only compatible with Bafang BBS01 BBS02 BBS03B BBSHD middle motor	6
	Wuxing Thumb Throttle for Bafang	1.Cable Length: 48cm 2.Connector : 3Pin Female Higo Cable 3.Fits for Handlebar diameter size:22.5mm	Only compatible with Bafang BBS01 BBS02 BBS03B BBSHD middle motor	5
	Bafang crank arms	1.Two holes distance is 170mm 2.Holes diameter: 22mm	The crank arms are for Bafang BBS01 BBS02 BBS03 BBSHD Mid Drive Motor.	9
	Canbus Bafang display 860C	1.With triangle connector Male 2.Cable length: 45cm 3.Fits for handlebar size: 22.2/25.4/31.8mm 4. With USB output charger port ,can charge mobile phone during cycling. 5.Work voltage:DC 36V/48/52V	Only compatible with Bafang mid motor M300 M400 M500 and M800,these ebike motors with speed limit 25KM/h	78

Photo	Name	Main spcs	Notice	Price USD/PCS
	Uart Bafang display 850C	1.The connector is 5 Pin waterproof IP65 2.Fit handlebar size:22.2/25.4/31.8mm 3. Output USB charge port,5V 500mA 4.With light sensor to control the ebike headlight.	Only compatible with Bafang BBS01 BBS02 BBS03B BBSHD middle motor	59
	Uart Bafang display 500C	1.The connector is 5 Pin waterproof IP65 2.Fit handlebar size:φ22.2mm 3. Vibration feedback:Touch button will vibrate	Only compatible with Bafang BBS01 BBS02 BBS03B BBSHD middle motor	42
	Uart Bafang display 500S (Black screen)	1.The connector is 5 Pin waterproof IP65 2.Fit handlebar size:φ22.2mm	Only compatible with Bafang BBS01 BBS02 BBS03B BBSHD middle motor	28
	Ebike light for Bafang Motor	1. Power:2.4W 2. Brightness:200 lumens (true brightness) 3. Input voltage: DC6V, 12V (Bafang BBS02 BBSHD Mid motor output 6V 2.4W for headlight,so our light is very suitable) 4. Material:CNC Aluminum Housing,high end ebike light. 5.Product size:38*38*42mm 6 Wire:Length 100cm 7. IPX5 waterproof,heavy rain waterproof	Fits for all ebikes motor provide output 6V / 12V 2.4W /3W for headlight.	13.2
Remark: 1.Above quotation are EXW price,not include shipping cost. 2.The quotation based on quantity 10pcs-50pcs.if order more.can get more discount.				